

Current-Limiting Power Fuses

Potential Transformer

9F60 Series, "E" Rated

EJ-1

Suitable for use indoors or in an enclosure



Product Description

Current-limiting fuses are designed to interrupt the high-fault currents and also the low-fault currents down to approximately 3 times their continuous current rating. Available from 0.625 to 15kV, from 0.5 to 3 Amps.

4.25" Clip Centers Clip-in Mounting Indoor or Enclosure

Catalog Number	Max. kV	Amp Rating	No. of Barrels	Indicating	Size ¹ /Diam Length	I/C Sym.	TCC min/max GES	Fuse Support, Indoor	Fuse Support, Outdoor	Disconnecting Switch, Indoor	Disconnecting Switch, Outdoor
9F60AAA003	0.625	3E	1	YES	A/0.812"/4.625"	100kA	8108/8109	-	-	-	-
9F60AAA005	0.625	5E	1	YES	A/0.812"/4.625"	100kA	8108/8109	-	-	-	-
9F60AAB001	2.75	1E	1	YES	A/0.812"/4.625"	60kA	8108/8109	-	-	-	-
9F60AAB002	2.75	2E	1	YES	A/0.812"/4.625"	60kA	8108/8109	-	-	-	-

¹Size A fuses are normally mounted directly on potential transformers. No supports, disconnect switches, or live parts are available for separate mounting.

6" Clip Centers Clip-in Mounting Indoor or Enclosure

Catalog Number	Max. kV	Amp Rating	No. of Barrels	Indicating	Spare Parts (Live Parts)	Spare Parts (Clips)	Size/Diam/Length	I/C Sym.	TCC min/max GES
9F60BBB001	2.75	1E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	60kA	8110/8111
9F60BBB002	2.75	2E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	60kA	8110/8111
9F60BBB003	2.75	3E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	60kA	8110/8111
9F60BBD905	5.5	0.5E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBD001	5.5	1E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBD002	5.5	2E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBD003	5.5	3E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBN905	5.5	0.5E	1	NO	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBN001	5.5	1E	1	NO	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBN002	5.5	2E	1	NO	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111
9F60BBN003	5.5	3E	1	NO	9F61BNW450	9F61BWW460	B/1.625"/7.375"	80kA	8110/8111

8.12" Clip Centers Clip-in Mounting Indoor or Enclosure

Catalog Number	Max. kV	Amp Rating	No. of Barrels	Indicating	Spare Parts (Live Parts)	Spare Parts (Clips)	Size/Diam/Length	I/C Sym.	TCC min/max GES	Fuse Support, Indoor
9F60BDB001	2.75	1E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	60kA	8110/8111	9F61ABB101
9F60BDB002	2.75	2E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	60kA	8110/8111	9F61ABB101
9F60BDB003	2.75	3E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	60kA	8110/8111	9F61ABB101
9F60BDD905	5.5	0.5E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABB101
9F60BDD001	5.5	1E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABB101
9F60BDD002	5.5	2E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABB101
9F60BDD003	5.5	3E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABB101
9F60BDE905	8.25	0.5E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABG101
9F60BDE001	8.25	1E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABG101
9F60BDE002	8.25	2E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABG101
9F60BDE003	8.25	3E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/9.50"	80kA	8110/8111	9F61ABG101

Current-Limiting Power Fuses

Potential Transformer

9F60 Series, "E" Rated

EJ-1

Suitable for use indoors or in an enclosure

11.5" Clip Centers Clip-in Mounting Indoor or Enclosure

Catalog Number	Max. kV	Amp Rating	No. of Barrels	Indicating	Spare Parts (Live Parts)	Spare Parts (Clips)	Size/Diam/Length	I/C Sym.	TCC min/max GES	Fuse support, Indoor
9F60BHH905	15.5	0.5E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/12.875"	120kA	8110/8111	9F61ADG101 (13.8kV, 95kV BIL), 9F61ADJ101 (14.4kV, 110kV BIL)
9F60BHH001	15.5	1E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/12.875"	120kA	8110/8111	9F61ADG101 (13.8kV, 95kV BIL), 9F61ADJ101 (14.4kV, 110kV BIL)
9F60BHH002	15.5	2E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/12.875"	120kA	8110/8111	9F61ADG101 (13.8kV, 95kV BIL), 9F61ADJ101 (14.4kV, 110kV BIL)
9F60BHH003	15.5	3E	1	YES	9F61BNW450	9F61BWW460	B/1.625"/12.875"	120kA	8110/8111	9F61ADG101 (13.8kV, 95kV BIL), 9F61ADJ101 (14.4kV, 110kV BIL)